

E-Z TRAIL...

HEAD HAULERS



"...it's the smoothest and straightest trailing wagon I have ever used. Since you have eliminated all steering wear points. I recommend you not tell anyone your secret. I am a Deere dealer that thought no one could build a better wagon, but I can't say that anymore..."
J.D., Fairfield, NC

The lower 4x6 rail is a "torsion" tube that easily flexes over rough terrain.

A Risk Management Tool

Moving wide grain heads doesn't need to be hazardous or worrisome. It can be as safe and easy as towing a legal width trailer on the road, across bridges, and through farm gates. With a Head Hauler, tight corners and low roof areas can be utilized for convenient inside storage.

Don't take a chance...safety is no accident!

In all thy ways
acknowledge Him
and He shall direct
thy paths. Prov. 3:6

PHONE 217/543-3471 • P.O. BOX 168 • ARTHUR, IL 61911

800-677-2802 www.e-ztrail.com

Head Haulers that help you move “ahead” at harvest time!

E-Z Trail Head Haulers are available in 5 sizes: 21’ with 12’4” wheel base, 26’ & 31’ with 15’10” wheel base, all with a 6 ton capacity. The 36’ & 40’ with 23’ wheel base have an 8 ton capacity. They are designed to fit all brands and models of combine grain and corn heads. Standard features like extendable “E-Z Hitch” tongue with spring lift assist, lifetime accurate trailing, and wrench-free quick adjusting at no extra cost...help you move ahead at a price that won’t set you back!

-- Available in **RED** or **GREEN**.



Special brackets are available to fit various models of flex draper heads



Patented two-way slider brackets can be easily adjusted to accommodate any brand of grain or corn head. Brackets are designed to fit round or square frames, channels, & gussets.



The long upper rail is easily adjusted using either a hand-crank screw Patent Pending (standard on 31’ & up) or a patented hand-tightened clamp.



Optional Lighting Kit: a necessity for use before sunrise and after sunset.



Standard tires for 21’-31’: Low profile 20.5x8-10 D Range (8 ply)

Optional: 20.5x8-10 F Range (12 ply) or 9.00-10 flotation tire

Standard tires for 36’ & 40’: 9.00-10 flotation tire (10 ply rating)

Optional: 26x12-12 F Range



Optional Ratchet Tie Down: 10,000# test nylon strap hooks into slots on bottom rail and secures heads without a scratch. Storage tray slides into top rail.



“Lifetime” accurate trailing is assured by E-Z Trail’s original steering centered around sealed tapered roller bearings, truck type ball joints and dual stops with 100% greater oversteer protection. All steering parts are weather protected for lifetime outdoor use.

Move ahead the E-Z way...always remember: A Safe Harvest is no Accident!